


RoHS Compliant


REV	ECN No.	DATE	REMARK
A	原始图档	2022.04.09	






NOTES:
1.MATERIAL AND FINISH
1.1 MATERIAL: STAINLESS STEEL,T=0.10MM.
1.2 FINISH: GOLD PLATED ON CONTACT AREA.
2.ELECTRICAL PERFORMANCE:
2.1 CURRENT RATING: 1.0A
2.2 VOLTAGE RATING: 15V AC/DC MAX..
2.3 CONTACT RESISTANCE: 100 MILIOHMS MAX.
2.4 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC,1 MINUTE
3.MECHANICAL PERFORMANCE:
3.1 NORMAL FORCE: 0.5±0.1N ON WORKING POSITION,
3.2 DURABILITY: 500 CYCLES.
4.OPERATION TEMPERATURE: -25℃~+85℃
5.PACKING: REEL & TAPE








RECOMMENDED PCB LAYOUT

TOLERANCE:±0.05MM
(FOR REFERENCE ONLY)



MATERIAL NO.:
JK-0R1400AG0179R
REVIEW TABLE FOR DETAILS

QUALITY SYMBOL
▽ = 0
▶ = 0

GENERAL TOLERANCES (UNLESS SPECIFIED)

X. ±0.25	X. ±4.0°
.X ±0.20	.X ±3.0°
.XX ±0.15	.XX ±2.0°

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J K F Technology Co.,Ltd. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

TITLE: 弹片 3.50*1.00*1.40H

ECN DESCRIPTION: RELEASE TO TOOLING

DRAWN BY: KATE DENG DATE:

CHECKED BY: FAND DATE: -----

APPROVED BY: Wang Yan DATE: ------

JKF connectivity J K F Technology Co.,Ltd

DOCUMENT NO.

SHEET NO.: 1 OF 1

DIMENSION STYLE: MM ONLY

DESIGN UNITS: METRIC

SCALE: 10:1

THIRD ANGLE PROJECTION

frame size: A4
Rev.A 2022.04.09