


RoHS Compliant


REV	ECN No.	DATE	REMARK
A	原始图档	2022.04.09	








备注：
1. 材质：SUS T=0.1mm
2. 电镀：接触区与焊接区镀金1u″
3. 额定电流：1A
4. 额定电压：10V DC
5. 接触电阻：80mΩ Max
6. 机械寿命：1500 Cycles
7. 盐雾测试：24H














RECOMMENDED PCB LAYOUT

MATERIAL NO.:
JK-0R1300AG0176R
REVIEW TABLE FOR DETAILS

QUALITY SYMBOL ▶ = 0 ▽ = 0

GENERAL TOLERANCES (UNLESS SPECIFIED)

X. ±0.25	X. ±4.0°
.X ±0.20	.X ±3.0°
.XX ±0.15	.XX ±2.0°

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J K F Technology Co.,Ltd. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

TITLE: 弹片 2.00*1.15*1.30H

ECN DESCRIPTION: RELEASE TO TOOLING

DRAWN BY: KATE DENG DATE:

CHECKED BY: FAND DATE: -----

APPROVED BY: Wang Yan DATE: ------

JKF connectivity J K F Technology Co.,Ltd

DOCUMENT NO.

SHEET NO.: 1 OF 1

DIMENSION STYLE	DESIGN UNITS	SCALE
MM ONLY	METRIC	10:1

THIRD ANGLE PROJECTION

frame size: A4
Rev.A 2022.04.09