















JK-BS3806AGB016R	16.50	12.50	10.00
JK-BS3805AGB016R	14.00	10.00	7.50
JK-BS3804AGB016R	11.50	7.50	5.00
JK-BS3803AGB016R	9.00	5.00	2.50
Part No.	DIMA	DIMB	DIMC



—NOTES—

1.Electrical:
Contact resistance:50m ohms max.
Dielectric withstanding voltage:250V RMS.
Insulation resistance:1000M ohms min.

2.Mechanical:
MATE AND UNMATE FORCE:
MATE FORCE:2.5kg MAX
UNMATE FORCE:0.5kg MIN
Durability:3000cycles MIN.

3.Environment:
Operating Temperature:—55°to+105°.

4.FINISH:
TERMINAL: GOLD Plated ALL Over NICKEL.

5.MATERIAL:
5.1.Housing:HI—TEMP Plastic,UL94V—0,black;
5.2.Terminal:Coppy alloy,T=0.12mm
5.3 Stator:Brass T=0.20mm

GENERAL TOLERANCES		UNIT	mm		
DISTANCE	X.	MATERIAL		SEE NOTES	
	X. ±0.25	FINISHED		SEE NOTES	
	.X ±0.20	APPROCED	KATE DENG		
	.XX ±0.15	CHECKED	KATE DENG		
	.XXX ±0.10	DESIGN	FAND		
ANGLE	X. ±3.0°	DRAWN	Wang Yan		
	.X ±2.0°				
	.XX ±1.0°				

REV.	ECN NO.	DESCRIPTION	DRAW/DATE	CHECKED	APPROVED

JKF Connectivity 杰康富精密电子有限公司 J K F precision Electronics Co., LTD

TITLE:	电池座 2.50PH 3.8H 有柱 3-6P							
PART NO.	JK-BS380XAGB016R							
DRAWING NO.								
SCALE	1:1	SIZE	A3	SHEET	1 OF 1	REV.	A	

Frame_A3
Rev.F2013/09/10